

Email: sales@hitechmarine.com.au
Website: www.hitechmarine.com.au

12 Uppill Place Wangara WA 6065





# Mercury 250 HP Verado

POA



# **Specifications**

## **Boat Details**

Price POA Boat Brand Mercury Model 250 HP (Verado) Length 0.00

Year 2023 Category Boat Engines and Outboards

Hull Style Hull Type

Power Type Stock Number Verado 1

### Disclaimer



Email: sales@hitechmarine.com.au

Website: www.hitechmarine.com.au

12 Uppill Place Wangara WA 6065

ConditionNewStateWestern AustraliaSuburbPERTHEngine MakeMercury

### Disclaimer



Email: sales@hitechmarine.com.au

Website: www.hitechmarine.com.au

12 Uppill Place Wangara WA 6065

## **Description**

A Smooth Operator

Built tough to withstand the rigors of saltwater operation, no outboard in the class offers more displacement. Great for deck, inflatable rigid hull, inshore fishing, multi-species fishing, offshore fishing, and runabout cuddy boats and tritoons.

The smooth, refined power of a V-8 4.6-liter powerhead delivers exhilarating acceleration and top speed to run offshore with confidence, while its generous displacement and robust design provide uncompromising durability and reliability. The Mercury-exclusive Advanced MidSection (AMS) and under-cowl noise management set the standard for smooth, quiet marine propulsion. These exciting new V-8 Verado outboards are wrapped in crisp, bold styling that makes an unmistakable statement on any transom.

HP / kW
250 / 186
Engine type
V-8
Disclosion and (CID/CC)
Displacement (CID/CC)
279 CID
Displacement (L)
4.6L
Cylinder Configuration
V8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves
Full throttle RPM
5200-6000



Email: sales@hitechmarine.com.au Website:

www.hitechmarine.com.au

12 Uppill Place Wangara WA 6065

Air induction				
Performance-Tuned Long-Runner Intake Manifold				
Fuel induction system				
Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization				
Alternator amp / Watt				
115-amp (1449 Watt) with Idle Charge				
Recommended fuel				
Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum				
Recommended oil				
NMMA Certified FCW SAE 10W-30				
Engine protection operator warning system				
SmartCraft Engine Guardian				
Starting				
Electric Start with SmartStart Protection				
Controls				
Standard: Digital Throttle & Shift (DTS)				
Steering				
Integrated Electro-Hydraulic Power-Steering				

# Disclaimer

Shaft length



Email: sales@hitechmarine.com.au

Website: www.hitechmarine.com.au

12 Uppill Place Wangara WA 6065

20" / 508 mm
25" / 635 mm
30" / 762 mm
Gearcase ratio
1.85:1
Dr. weight *Lightest model available
Dry weight *Lightest model available
600 lbs / 272 kgs
CARB star rating
3
Bore and stroke
3.6 in x 3.4 in / 92 mm x 86 mm
Ignition
SmartCraft PCM 112 Digital Inductive
Cooling system
Water-cooled with thermostat
Gear shift
F-N-R
Gearcase options
5.44"

### Disclaimer



Email: sales@hitechmarine.com.au
Website: www.hitechmarine.com.au

12 Uppill Place Wangara WA 6065

Trim system		
Power trim and tilt		
Exhaust system		
Through prop		
Color		
Cold Fusion White		
Pearl Fusion White		
Phantom Black		
Warm Fusion White		
Oil Capacity		
7.0 Quarts / 6.6 Liters		
Maximum Trim Range		
20° (-6° to 14°)		
Maximum Tilt Range		
73° (-6° to 67°)		
Features Horse Power (hp)	250	
	200	

# Engine Details Engine Make

Engine Make Mercury
Displacement 4.6
Horse Power 250

Fuel Type Premium Unleaded

8

Drive Type

### Disclaimer